




OPUS is a contemporary round tube radiator. It has a simple, yet sleek design that blends effortlessly into its surrounding. It is a stylish and functional radiator, with high heat outputs, and comes in a range of sizes and models. Standard colour is an attractive white (RAL 9016) but other colour options are available, see page 266.

- OPUS is available in eight different sizes
- Widths range from 324mm - 1000mm
- Heights vary from 468mm - 2000mm














OPUS HORIZONTAL

OPUS VERTICAL

# OPUS

## General specification & technical information


-  **CERTIFICATION**  
Manufactured and tested to BS EN 442 & EN 442. Carries the CE & UKCA Mark. Produced under a quality management system - ISO 9001:2015, environmental management system - ISO 14001:2015 and Occupational health and safety management system - OHSAS 18001.
-  **GUARANTEE**  
10 year guarantee from date of purchase against manufacturing defects.
-  **COLOUR**  
Standard finish is white (RAL 9016). For other special colour options please see page 266.
-  **MATERIAL**  
Manufactured from steel.
-  **SYSTEM**  
2 pipe pumped indirect domestic and commercial heating applications.

-  **CONNECTIONS**  
Vertical: 6 x 1/2" BSP. Horizontal: 4 x 1/2" BSP.
-  **AIR VENTS**  
Included in the packaging.
-  **OPERATING PRESSURES**  
Tested to a pressure of 13 bar. Working pressure of up to 10 bar.
-  **OPERATING TEMPERATURE**  
Maximum 100°C.
-  **DELIVERY**  
Non-stocked item: 4 - 5 weeks.
-  **VALVES**  
Please see page 225.

For more general information, please see page 264.

### Weights & water contents per metre length


Type	Weight (kg)	Water Content (l)
MEZV1	14.49	6.93
MEZV2	20.93	10.01
MEZV3	27.37	13.09
MEZV4	33.81	16.17
MEZH1	7.20	3.32
MEZH2	9.28	4.34
MEZH3	12.01	5.54
MEZH4	15.38	7.24




### Connection options

6 x 1/2" BSP


Vertical (Universal Connection)



Vertical connection options without the need for an insert




Vertical connection options which require an insert





4 x 1/2" BSP

Horizontal




Key


-  Baffle Without Insert
-  Baffle With Insert (manual insertion required on universal connections - see above)

### Mounting positions, dimensions & wall brackets


OPUS Horizontal



OPUS Vertical



Wall Bracket Dimensions



NB: All measurements are nominal.

### Heat outputs

OPUS vertical

Order Code	Nominal Height (H) (mm)	Nominal Length (L) (mm)	No. of Tubes	Heat Outputs @ ΔT 50°C		Heat Outputs @ ΔT 30°C		n-Coefficients
				Watts	Btu/h	Watts	Btu/h	
MEZV1*	2000	324	9	803	2740	413	1409	1.304
MEZV2*	2000	468	13	1160	3958	596	2034	1.304
MEZV3*	2000	612	17	1516	5173	779	2658	1.304
MEZV4*	2000	756	21	1873	6391	1146	3910	1.304

OPUS horizontal

MEZH1*	468	600	13	403	1375	212	723	1.258
MEZH2*	612	600	17	516	1761	271	925	1.262
MEZH3*	468	1000	13	672	2293	353	1204	1.258
MEZH4*	612	1000	17	860	2934	451	1539	1.262

\*Non-stock - made to order only.